



**Specifications Noxion LED Downlight Apollo 20W 2300lm 60D - 830 Warm White | 220mm - Cutout 200mm - Alu Reflector - UGR <19**

[View Product](#)

## General Information

|                          |                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------|
| SKU                      | 243082                                                                                |
| EAN                      | 8719157035019                                                                         |
| Brand                    | Noxion                                                                                |
| Manufacturer Name        | Noxion LED Downlight Apollo 20W 2300LM 3000K Cutout Ø200mm Frame Ø220mm Alu Reflector |
| Any Lamp all-in warranty | 6 Years                                                                               |
| Average Lifetime (h)     | 60000                                                                                 |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Including bulb              | Yes               |
| Driver Included             | Yes               |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 60                             |
| Luminous Efficacy (lm/W) | 125                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 140                            |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Finish of Reflector      | Aluminium                      |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Apollo            |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 141 |
| Diameter (mm) | 220 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy return process**