



Specifications Multipack 5x Noxion LED Panel Delta Value V5 Backlit 28W 3920lm 830/840 CCT | 60x60cm - < 22 - Philips Driver

[View Product](#)

General Information

|                          |                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------|
| SKU                      | 259058                                                                                          |
| EAN                      | 8719157079488                                                                                   |
| Brand                    | Noxion                                                                                          |
| Manufacturer Name        | Multipack 5x Noxion LED Panel Delta Value V5.1 28W 3920lm 2CCT 600*600 (Philips Driver) Backlit |
| Any Lamp all-in warranty | 6 Years                                                                                         |
| Average Lifetime (h)     | 90000                                                                                           |
| Series                   | Delta Value                                                                                     |

Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |
| Luminous Efficacy (lm/W)    | 140                              |
| IP-rating                   | IP20                             |
| Impact Protection (IK)      | IK02 - 0.20 joule                |

|                       |               |
|-----------------------|---------------|
| Fixture Connection    | Push Terminal |
| Finish of Reflector   | Frosted       |
| Power factor          | >0.90         |
| Product Type Category | LED Panel     |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -20 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

## Sensor Information

Type of sensor No Sensor

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

